

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : Dansac Skin Lotion
Product code : 70005-0001, 71000-0000

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : Ostomy use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier	Manufacturer
Hollister ULC	Dansac A/S
Foxford Road	Lille Kongevej 304
Rehins, Ballina	Fredensborg 3480 Denmark
County Mayo, Ireland F26 F3X5	T: +45 48465000
Tel: +353 96 60600	www.dansac.com
Email: baehsinfo@Hollister.com	
Manufacturer web: www.hollister.com	

Global corporate headquarters
Hollister Incorporated
2000 Hollister Drive
Libertyville, Illinois 60048
847-680-1000
www.Hollister.com

1.4. Emergency telephone number

Emergency number : +45 48465000; +45 82 12 12 12 (Denmark Poison Control (Giftlinjen))

SECTION 2: Hazards identification

This product is regulated as a medical device in European Economic Area (EEA) and therefore, is exempt for the requirement to provide a CLP/REACH compliant SDS as it is medical device used in direct physical contact with the human body per Medical Device Regulation (MDR) (2017/745). The information contained within this SDS is provided for the benefit of non-clinical personnel as a guide to handling the product in a non-medical setting. In other regions, it may be regulated as a medical device, a cosmetic or not regulated.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3 H226
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour.

2.2. Label elements

The product is assessed and supplied with a safety data sheet in accordance with Regulation (EC) no 1272/2008. Labelling of the product is prepared in accordance with Medical Device Regulation (MDR) (2017/745) on medical devices and local legislation.

Dansac Skin Lotion

Safety Data Sheet

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

:



GHS02

Signal word (CLP)

: Warning

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.

Precautionary statements (CLP)

: CLP Label elements are not applicable for medical devices used in direct physical contact with the human body. The product is to be labelled according to the requirements of the medical devices regulations.

2.3. Other hazards

other hazards which do not result in classification

: Product contains ethanol. Care should be observed to ensure any potential vapours do not pose a fire hazard.

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1 %.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	8 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Hydrochloric acid substance with a Community workplace exposure limit	CAS-No.: 7647-01-0 EC-No.: 231-595-7 EC Index-No.: 017-002-01-X	< 0,1	Skin Corr. 1A, H314 STOT SE 3, H335

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Hydrochloric acid	CAS-No.: 7647-01-0 EC-No.: 231-595-7 EC Index-No.: 017-002-01-X	(10 \leq C < 25) Skin Irrit. 2, H315 (10 \leq C < 25) Eye Irrit. 2, H319 (10 \leq C \leq 100) STOT SE 3, H335 (25 \leq C \leq 100) Skin Corr. 1B, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Get medical advice/attention if you feel unwell.

First-aid measures after inhalation

: If experiencing respiratory symptoms: Remove person to fresh air and keep comfortable for breathing.

Dansac Skin Lotion

Safety Data Sheet

First-aid measures after skin contact	: Not expected to present a significant hazard under anticipated conditions of normal use. If skin irritation or rash occurs: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: Overexposure to vapours may result in cough.
Symptoms/effects after eye contact	: May cause slight temporary irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. Water spray. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour. On combustion, forms: carbon oxides (CO and CO ₂). Nitrogen oxides (NO _x).
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: No special protection required.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment	: No special protection required.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Wipe up with absorbent material (for example cloth).
Other information	: Dispose of in a safe manner in accordance with local/national regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: "Disposal considerations".

Dansac Skin Lotion

Safety Data Sheet

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Use good personal hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Do not overheat the product. Keep out of direct sunlight. Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Incompatible materials : Oxidizing materials. Strong acids. Alkalis.

7.3. Specific end use(s)

See Section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Hydrochloric acid (7647-01-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Hydrogen chloride
IOEL TWA	8 mg/m ³
IOEL TWA [ppm]	5 ppm
IOEL STEL	15 mg/m ³
IOEL STEL [ppm]	10 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Austria - Occupational Exposure Limits	
Local name	Chlorwasserstoff (Hydrogenchlorid; Salzsäure)
MAK (OEL TWA)	8 mg/m ³
MAK (OEL TWA) [ppm]	5 ppm
MAK (OEL STEL)	15 mg/m ³
MAK (OEL STEL) [ppm]	10 ppm
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Hydrogène (chlorure d') # Waterstofchloride
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Хлороводород

Dansac Skin Lotion

Safety Data Sheet

Hydrochloric acid (7647-01-0)	
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Vodikov klorid
GVI (OEL TWA) [1]	8 mg/m ³
GVI (OEL TWA) [2]	5 ppm
KGVI (OEL STEL)	15 mg/m ³
KGVI (OEL STEL) [ppm]	10 ppm
Remark	Direktiva: 2000/39/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граничним vrijednostima izloženosti i biološkim граничним vrijednostima (NN 1/2021)
Cyprus - Occupational Exposure Limits	
Local name	Υδροχλώριο
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	Chlorovodík
PEL (OEL TWA)	8 mg/m ³
PEL (OEL TWA) [ppm]	5,3 ppm
NPK-P (OEL C)	15 mg/m ³
NPK-P (OEL C) [ppm]	9,9 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Hydrogenchlorid (Chlorbrinte)
OEL TWA [1]	8 mg/m ³
OEL TWA [2]	5 ppm
OEL STEL	8 mg/m ³
OEL STEL	5 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi)

Dansac Skin Lotion

Safety Data Sheet

Hydrochloric acid (7647-01-0)	
Regulatory reference	BEK nr 202 af 21/02/2023
Estonia - Occupational Exposure Limits	
Local name	Vesinikkloriid
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)
Finland - Occupational Exposure Limits	
Local name	Kloorivety, vedetön
HTP (OEL STEL)	7,6 mg/m ³ (anhydrous and in solution)
HTP (OEL STEL) [ppm]	5 ppm (anhydrous and in solution)
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Chlorure d'hydrogène (Acide chlorhydrique)
VLE (OEL C/STEL)	7,6 mg/m ³ (restrictive limit)
VLE (OEL C/STEL) [ppm]	5 ppm (restrictive limit)
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Hydrogenchlorid
AGW (OEL TWA) [1]	3 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	2 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Peak exposure limitation factor	2(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	Hydrogen chloride
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)

Dansac Skin Lotion

Safety Data Sheet

Hydrochloric acid (7647-01-0)	
Greece - Occupational Exposure Limits	
Local name	Υδροχλωρίο
OEL TWA	7 mg/m ³
OEL TWA	5 ppm
OEL STEL	7 mg/m ³
OEL STEL	5 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	SÓSAV
AK (OEL TWA)	8 mg/m ³
CK (OEL STEL)	165 mg/m ³
Remark	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát), m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármát); EU1 (2000/39/EK irányelvben közölt érték); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Hydrogen chloride
OEL TWA [1]	8 mg/m ³
OEL TWA [2]	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	Acido cloridrico
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Hlorūdeņradis
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325

Dansac Skin Lotion

Safety Data Sheet

Hydrochloric acid (7647-01-0)	
Lithuania - Occupational Exposure Limits	
Local name	Vandenilio chloridas
IPRV (OEL TWA)	8 mg/m ³
IPRV (OEL TWA) [ppm]	5 ppm
TPRV (OEL STEL)	15 mg/m ³
TPRV (OEL STEL) [ppm]	10 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Chlorure d'hydrogène
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Hydrogen chloride
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Netherlands - Occupational Exposure Limits	
Local name	Zoutzuur
TGG-8u (OEL TWA)	8 mg/m ³
TGG-8u (OEL TWA) [ppm]	5 ppm
TGG-15min (OEL STEL)	15 mg/m ³
TGG-15min (OEL STEL) [ppm]	10 ppm
Regulatory reference	Arbeidsomstandighedenregeling 2023
Poland - Occupational Exposure Limits	
Local name	Chlorowodór
NDS (OEL TWA)	5 mg/m ³
NDSch (OEL STEL)	10 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Ácido clorídrico
OEL TWA	8 mg/m ³ (indicative limit value)
OEL TWA	5 ppm (indicative limit value)
OEL STEL	15 mg/m ³ (indicative limit value)

Dansac Skin Lotion

Safety Data Sheet

Hydrochloric acid (7647-01-0)	
OEL STEL	10 ppm (indicative limit value)
OEL C	2 mg/m ³
OEL C	2 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Remark	A4 (Agente não classificável como carcinogénico no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Acid clorhidric/Clorură de hidrogen
OEL TWA	8 mg/m ³
OEL TWA	5 ppm
OEL STEL	15 mg/m ³
OEL STEL	10 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovakia - Occupational Exposure Limits	
Local name	Chlorovodík
NPHV (OEL TWA) [1]	8 mg/m ³
NPHV (OEL TWA) [2]	5 ppm
NPHV (OEL STEL)	15 mg/m ³
NPHV (OEL STEL) [ppm]	10 ppm
NPHV (OEL C)	15 mg/m ³
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	vodikov klorid, brezvodni (klorovodik, brezvodni)
OEL TWA	8 mg/m ³ (anhydrous)
OEL TWA	5 ppm (anhydrous)
OEL STEL	15 mg/m ³ (anhydrous)
OEL STEL	10 ppm (anhydrous)
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	7,6 mg/m ³ (indicative limit value)
VLA-ED (OEL TWA) [2]	5 ppm (indicative limit value)
VLA-EC (OEL STEL)	15 mg/m ³
VLA-EC (OEL STEL) [ppm]	10 ppm
Sweden - Occupational Exposure Limits	
Local name	Saltsyra (Väteklorid)
NGV (OEL TWA)	3 mg/m ³
NGV (OEL TWA) [ppm]	2 ppm

Dansac Skin Lotion

Safety Data Sheet

Hydrochloric acid (7647-01-0)	
KTV (OEL STEL)	6 mg/m ³
KTV (OEL STEL) [ppm]	4 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
Norway - Occupational Exposure Limits	
Local name	Hydrogenklorid (Saltsyre)
Takverdi (OEL C) [1]	7 mg/m ³
Takverdi (OEL C) [2]	5 ppm
Remark	E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
USA - ACGIH - Occupational Exposure Limits	
Local name	Hydrogen chloride
ACGIH OEL C [ppm]	2 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2023
Potassium hydroxide (1310-58-3)	
Austria - Occupational Exposure Limits	
Local name	Kaliumhydroxid
MAK (OEL TWA)	2 mg/m ³ (inhalable fraction)
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Potassium (hydroxyde de) # Kaliumhydroxide
OEL STEL	2 mg/m ³
Remark	M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkprocédé moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Калиева основа
OEL TWA	2 mg/m ³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Kalijev hidroksid; kaustična potaša

Dansac Skin Lotion

Safety Data Sheet

Potassium hydroxide (1310-58-3)	
KGVI (OEL STEL)	2 mg/m ³
Regulatory reference	Pravidník o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	Hydroxid draselný
PEL (OEL TWA)	1 mg/m ³
NPK-P (OEL C)	2 mg/m ³
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Kaliumhydroxid
OEL STEL	2 mg/m ³
OEL C	2 mg/m ³
Regulatory reference	BEK nr 202 af 21/02/2023
Estonia - Occupational Exposure Limits	
Local name	Kaaliumhüdrosiid
OEL TWA	2 mg/m ³
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)
Finland - Occupational Exposure Limits	
Local name	Kaliumhydroksidi
HTP (OEL C)	2 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Potassium (hydroxyde de)
VLE (OEL C/STEL)	2 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Υδροξείδιο του καλίου
OEL TWA	2 mg/m ³
OEL STEL	2 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	KÁLIUM-HIDROXID
AK (OEL TWA)	2 mg/m ³
CK (OEL STEL)	2 mg/m ³
Remark	m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármát); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)

Dansac Skin Lotion

Safety Data Sheet

Potassium hydroxide (1310-58-3)	
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Potassium hydroxide
OEL STEL	2 mg/m ³
Regulatory reference	Chemical Agents Code of Practice 2021
Poland - Occupational Exposure Limits	
Local name	Wodorotlenek potasu
NDS (OEL TWA)	0,5 mg/m ³
NDSch (OEL STEL)	1 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Hidróxido de potássio
OEL C	2 mg/m ³
OEL C	2 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Spain - Occupational Exposure Limits	
Local name	Hidróxido de potasio
VLA-EC (OEL STEL)	2 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
Local name	Kaliumhydroxid
NGV (OEL TWA)	1 mg/m ³ (inhalable fraction)
KTV (OEL STEL)	2 mg/m ³ (inhalable fraction)
Remark	3 (Med inhalerbar fraktion menas den mängd partiklar, av totalmängden partiklar i luften, som man inandas genom näsa och mun)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
Norway - Occupational Exposure Limits	
Local name	Kaliumhydroksid
Takverdi (OEL C) [1]	2 mg/m ³
Regulatory reference	FOR-2021-06-28-2248
USA - ACGIH - Occupational Exposure Limits	
Local name	Potassium hydroxide
ACGIH OEL C	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2023
Ethanol (64-17-5)	
Austria - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)

Dansac Skin Lotion

Safety Data Sheet

Ethanol (64-17-5)	
MAK (OEL TWA)	1900 mg/m ³
MAK (OEL TWA) [ppm]	1000 ppm
MAK (OEL STEL)	3800 mg/m ³ (3x 60(Mow) min)
MAK (OEL STEL) [ppm]	2000 ppm (3x 60(Mow) min)
OEL C	3800 mg/m ³
OEL C	2000 ppm
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Alcool éthylique # Ethanol
OEL TWA	1907 mg/m ³
OEL TWA	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Етилов алкохол
OEL TWA	1000 mg/m ³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Etanol; etil-alkohol
GVI (OEL TWA) [1]	1900 mg/m ³
GVI (OEL TWA) [2]	1000 ppm
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)
PEL (OEL TWA)	1000 mg/m ³
PEL (OEL TWA) [ppm]	522 ppm
NPK-P (OEL C)	3000 mg/m ³
NPK-P (OEL C) [ppm]	1566 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)
OEL TWA [1]	1900 mg/m ³
OEL TWA [2]	1000 ppm
OEL STEL	3800 mg/m ³
OEL STEL	2000 ppm
Regulatory reference	BEK nr 202 af 21/02/2023
Estonia - Occupational Exposure Limits	
Local name	Etanool (etüülalkohol)

Dansac Skin Lotion

Safety Data Sheet

Ethanol (64-17-5)	
OEL TWA	1000 mg/m ³
OEL TWA	500 ppm
OEL STEL	1900 mg/m ³
OEL STEL	1000 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)
Finland - Occupational Exposure Limits	
Local name	Etanoli
HTP (OEL TWA) [1]	1900 mg/m ³
HTP (OEL TWA) [2]	1000 ppm
HTP (OEL STEL)	2500 mg/m ³
HTP (OEL STEL) [ppm]	1300 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Alcool éthylique
VME (OEL TWA)	1900 mg/m ³
VME (OEL TWA) [ppm]	1000 ppm
VLE (OEL C/STEL)	9500 mg/m ³
VLE (OEL C/STEL) [ppm]	5000 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Ethanol
AGW (OEL TWA) [1]	380 mg/m ³
AGW (OEL TWA) [2]	200 ppm
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Greece - Occupational Exposure Limits	
Local name	Αιθνόλη
OEL TWA	1900 mg/m ³
OEL TWA	1000 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	ETIL-ALKOHOL
AK (OEL TWA)	1900 mg/m ³
CK (OEL STEL)	3800 mg/m ³

Dansac Skin Lotion

Safety Data Sheet

Ethanol (64-17-5)	
Remark	N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Ethanol [Ethyl alcohol]
OEL TWA [1]	1900 mg/m ³
OEL TWA [2]	1000 ppm
OEL STEL	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
Local name	Etilspirts (etanols)
OEL TWA	1000 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Etanolis (etilo alkoholis)
IPRV (OEL TWA)	1000 mg/m ³
IPRV (OEL TWA) [ppm]	500 ppm
TPRV (OEL STEL)	1900 mg/m ³
TPRV (OEL STEL) [ppm]	1000 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Netherlands - Occupational Exposure Limits	
Local name	Ethanol
TGG-8u (OEL TWA)	260 mg/m ³
TGG-8u (OEL TWA) [ppm]	137 ppm
TGG-15min (OEL STEL)	1900 mg/m ³
TGG-15min (OEL STEL) [ppm]	1000 ppm
Remark	Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
MAC chemical category	Skin notation
Regulatory reference	Arbeidsomstandighedenregeling 2023
Poland - Occupational Exposure Limits	
Local name	Etanol (alkohol etylowy)
NDS (OEL TWA)	1900 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Etanol (Álcool etílico)
OEL STEL	1000 ppm
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

Dansac Skin Lotion

Safety Data Sheet

Ethanol (64-17-5)	
Remark	A3 (Agente carcinogénico confirmado nos animais de laboratorio con relevância desconhecida no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Alcool etilic/Etanol
OEL TWA	1900 mg/m ³
OEL TWA	1000 ppm
OEL STEL	9500 mg/m ³
OEL STEL	5000 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovakia - Occupational Exposure Limits	
Local name	Etylalkohol (etanol)
NPHV (OEL TWA) [1]	960 mg/m ³
NPHV (OEL TWA) [2]	500 ppm
NPHV (OEL STEL)	1920 mg/m ³
NPHV (OEL STEL) [ppm]	1000 ppm
NPHV (OEL C)	1920 mg/m ³
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	etanol (etilalkohol)
OEL TWA	960 mg/m ³
OEL TWA	500 ppm
OEL STEL	1920 mg/m ³
OEL STEL	1000 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Etanol (Alcohol etílico)
VLA-ED (OEL TWA) [1]	1910 mg/m ³
VLA-ED (OEL TWA) [2]	1000 ppm
VLA-EC (OEL STEL)	1910 mg/m ³
VLA-EC (OEL STEL) [ppm]	1000 ppm
Remark	s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas Base de datos de productos fitosanitarios http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT

Dansac Skin Lotion

Safety Data Sheet

Ethanol (64-17-5)	
Sweden - Occupational Exposure Limits	
Local name	Etanol
NGV (OEL TWA)	1000 mg/m ³
NGV (OEL TWA) [ppm]	500 ppm
KTV (OEL STEL)	1900 mg/m ³
KTV (OEL STEL) [ppm]	1000 ppm
Remark	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
Norway - Occupational Exposure Limits	
Local name	Etanol
Grenseverdi (OEL TWA) [1]	950 mg/m ³
Grenseverdi (OEL TWA) [2]	500 ppm
Korttidsverdi (OEL STEL)	1187,5 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	625 ppm (value calculated)
Regulatory reference	FOR-2021-06-28-2248
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanol
ACGIH OEL STEL [ppm]	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2023
Isopropyl alcohol (67-63-0)	
Austria - Occupational Exposure Limits	
Local name	2-Propanol (Isopropanol; Isopropylalkohol)
MAK (OEL TWA)	500 mg/m ³
MAK (OEL TWA) [ppm]	200 ppm
MAK (OEL STEL)	2000 mg/m ³ (4x 15(Miw) min) 2000 mg/m ³ (4x 30(Miw) min) (Kurzzzeitwert für Großguss gilt bis 31.12.2013)
MAK (OEL STEL) [ppm]	800 ppm (4x 15(Miw) min) 800 ppm (4x 30(Miw) min) (Kurzzzeitwert für Großguss gilt bis 31.12.2013)
OEL chemical category	Group C Carcinogen by manufacturing of strong Acid process, Group C Carcinogen by manufacturing of strong Acid process
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Alcool isopropylique # Isopropylalcohol
OEL TWA	500 mg/m ³
OEL TWA	200 ppm
OEL STEL	1000 mg/m ³

Dansac Skin Lotion

Safety Data Sheet

Isopropyl alcohol (67-63-0)	
OEL STEL	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Изопропилов алкохол
OEL TWA	980 mg/m ³
OEL STEL	1225 mg/m ³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Propan-2-ol; izopropil-alkohol; izopropanol
GVI (OEL TWA) [1]	999 mg/m ³
GVI (OEL TWA) [2]	400 ppm
KGVI (OEL STEL)	1250 mg/m ³
KGVI (OEL STEL) [ppm]	500 ppm
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граничним vrijednostima izloženosti i biološkim граничним vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Propan-2-ol
BLV	50 mg/l Parameter: Acetone - Medium: blood - Sampling time: at the end of the work shift 50 mg/l Parameter: Acetone - Medium: urine - Sampling time: at the end of the work shift
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граничним vrijednostima izloženosti i biološkim граничним vrijednostima (NN 91/2018)
Czech Republic - Occupational Exposure Limits	
Local name	2-Propanol (Isopropanol; Izopropylalkohol)
PEL (OEL TWA)	500 mg/m ³
PEL (OEL TWA) [ppm]	200 ppm
NPK-P (OEL C)	1000 mg/m ³
NPK-P (OEL C) [ppm]	400 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Isopropylalkohol (Isopropanol; 2-Propanol; sec-Propylalkohol)
OEL TWA [1]	490 mg/m ³
OEL TWA [2]	200 ppm
OEL STEL	980 mg/m ³
OEL STEL	400 ppm
Regulatory reference	BEK nr 202 af 21/02/2023
Estonia - Occupational Exposure Limits	
Local name	2-propanool (isopropüülalkohol, isopropanool)

Dansac Skin Lotion

Safety Data Sheet

Isopropyl alcohol (67-63-0)	
OEL TWA	350 mg/m ³
OEL TWA	150 ppm
OEL STEL	600 mg/m ³
OEL STEL	250 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)
Finland - Occupational Exposure Limits	
Local name	2-Propanoli
HTP (OEL TWA) [1]	500 mg/m ³
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	620 mg/m ³
HTP (OEL STEL) [ppm]	250 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Alcool isopropylique
VLE (OEL C/STEL)	980 mg/m ³
VLE (OEL C/STEL) [ppm]	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Propan-2-ol
AGW (OEL TWA) [1]	500 mg/m ³
AGW (OEL TWA) [2]	200 ppm
AGW (OEL C)	1000 mg/m ³
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Propan-2-ol
Biological limit value	25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift
Regulatory reference	TRGS 903
Greece - Occupational Exposure Limits	
Local name	Ισοπροπυλική αλκοόλη
OEL TWA	980 mg/m ³
OEL TWA	400 ppm
OEL STEL	1225 mg/m ³
OEL STEL	500 ppm

Dansac Skin Lotion

Safety Data Sheet

Isopropyl alcohol (67-63-0)	
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	IZOPROPIL-ALKOHOL
AK (OEL TWA)	500 mg/m ³
CK (OEL STEL)	1000 mg/m ³
Remark	b (Bőrön át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat); R (Azok az anyagok, amelyek egészségkárosító hatása RÖVID expozíció hatására jelentkezik)
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Hungary - Biological Exposure Indices	
Local name	Izopropil-alkohol (2-Propanol)
BEI	25 mg/l Biológiai expozíciós (hatás) mutató: acetone - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 430 µmol/l Biológiai expozíciós (hatás) mutató: acetone - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén)
Remark	A foglalkozási vegyi expozíció esetén ajánlott biológiai expozíciós és hatásmutatók határértékei
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Isopropyl alcohol [Propan-2-ol]
OEL TWA [2]	200 ppm
OEL STEL	400 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body)
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	2-Propanol
BMGV	40 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B (Background), Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
Latvia - Occupational Exposure Limits	
Local name	Izopropanols (2-propanols, izopropilspirts, 1-metil-1-etanols)
OEL TWA	350 mg/m ³
OEL STEL	600 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	2-propanolis (izopropanolis, izopropilo alkoholis)

Dansac Skin Lotion

Safety Data Sheet

Isopropyl alcohol (67-63-0)	
IPRV (OEL TWA)	350 mg/m ³
IPRV (OEL TWA) [ppm]	150 ppm
TPRV (OEL STEL)	600 mg/m ³
TPRV (OEL STEL) [ppm]	250 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	650 mg/m ³
TGG-15min (OEL STEL)	0 mg/m ³
Poland - Occupational Exposure Limits	
Local name	Propan-2-ol (izopropylowy alkohol)
NDS (OEL TWA)	900 mg/m ³
NDSch (OEL STEL)	1200 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	2-Propanol (isopropanol ou álcool isopropílico)
OEL TWA	200 ppm
OEL STEL	400 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Remark	A4 (Agente não classificável como carcinogénico no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	2-Propanol
BEI	40 mg/l Parâmetro: Acetona - Meio: urina - Momento da amostragem: Fim do turno no fim da semana de trabalho - Notação: Vb (Valor basal), Ne (Não específico)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Alcool izopropilic/2-Propanol
OEL TWA	200 mg/m ³
OEL TWA	81 ppm
OEL STEL	500 mg/m ³
OEL STEL	203 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Romania - Biological limit values	
Local name	Alcool izopropilic
BLV	50 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)

Dansac Skin Lotion

Safety Data Sheet

Isopropyl alcohol (67-63-0)	
Slovakia - Occupational Exposure Limits	
Local name	Izopropylalkohol (propán-2-ol)
NPHV (OEL TWA) [1]	500 mg/m ³
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL STEL)	1000 mg/m ³
NPHV (OEL STEL) [ppm]	400 ppm
NPHV (OEL C)	1000 mg/m ³
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	propan-2-ol (izopropilalkohol; izopropanol)
OEL TWA	500 mg/m ³
OEL TWA	200 ppm
OEL STEL	1000 mg/m ³
OEL STEL	400 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	2-propanol
BLV	25 mg/l Parameter: aceton - Biološki vzorec: kri - Čas vzorčenja: ob koncu delovne izmene 25 mg/l Parameter: aceton - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Isopropanol (Alcohol isopropílico)
VLA-ED (OEL TWA) [1]	500 mg/m ³
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1000 mg/m ³
VLA-EC (OEL STEL) [ppm]	400 ppm
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas Base de datos de productos fitosanitarios http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Spain - Biological limit values	
Local name	Isopropanol (Alcohol isopropílico)
BLV	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of workweek
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT

Dansac Skin Lotion

Safety Data Sheet

Isopropyl alcohol (67-63-0)	
Sweden - Occupational Exposure Limits	
Local name	Isopropanol
NGV (OEL TWA)	350 mg/m ³
NGV (OEL TWA) [ppm]	150 ppm
KTV (OEL STEL)	600 mg/m ³
KTV (OEL STEL) [ppm]	250 ppm
Remark	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
Norway - Occupational Exposure Limits	
Local name	2-propanol (Isopropanol)
Grenseverdi (OEL TWA) [1]	245 mg/m ³
Grenseverdi (OEL TWA) [2]	100 ppm
Korttidsverdi (OEL STEL)	306,25 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	150 ppm (value calculated)
Regulatory reference	FOR-2021-06-28-2248
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2023
USA - ACGIH - Biological Exposure Indices	
Local name	2-PROPANOL
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift at end of workweek (background, nonspecific)
Regulatory reference	ACGIH 2023

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	No additional information available.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Dansac Skin Lotion

Safety Data Sheet

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Not required for normal conditions of use. Normal use of this product shall imply use in accordance with the instructions on the packaging. Ensure adequate ventilation.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Not required for normal conditions of use. If there is a risk of eye contact: Use suitable eye protection. ISO 16321-1

8.2.2.2. Skin protection

Hand protection:

Not required for normal conditions of use. In case of repeated or prolonged exposure : Wear suitable gloves resistant to chemical penetration. ISO 374-1

8.2.2.3. Respiratory protection

Respiratory protection:

Not required for normal conditions of use. In case of insufficient ventilation, wear suitable respiratory equipment (EN 136/140/145). Wear appropriate breathing apparatus if air renewal not sufficient to maintain dust/vapour under TLV

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Appearance	: Lotion.
Odour	: alcohol odour.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 81 °C
Flammability	: Flammable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 51 – 54 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 8 - 9
Viscosity, kinematic	: Not available
Solubility	: Dispersible (partial solubilisation) in: Water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 18 mm Hg (@ 0 °C)
Vapour pressure at 50°C	: Not available
Density	: 0,84
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (Air=1)
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

Dansac Skin Lotion

Safety Data Sheet

9.2.2. Other safety characteristics

Lower Flammable limit: : 3.3 % by volume as ethanol
Upper Flammable limit: : 19 % by volume as ethanol

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing materials. Strong acids. Alkalis.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition can lead to the release of irritating gases and vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg (Source: NLM_CIP)
LD50 oral	10470 mg/kg bodyweight
LD50 dermal	15800 mg/kg bodyweight
LC50 Inhalation - Rat	133,8 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	> 99999 mg/l
LC50 Inhalation - Rat (Vapours)	116,9 mg/l Source: ECHA

Skin corrosion/irritation : Not classified (On basis of test data)

Hydrochloric acid (7647-01-0)	
pH	1,1 (conc: 0.1 N (solution))

Ethanol (64-17-5)	
pH	7 Source: chemicalbook

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

Hydrochloric acid (7647-01-0)	
pH	1,1 (conc: 0.1 N (solution))

Dansac Skin Lotion

Safety Data Sheet

Ethanol (64-17-5)	
pH	7 Source: chemicalbook
Respiratory or skin sensitisation	: Not classified (On basis of test data)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Hydrochloric acid (7647-01-0)	
IARC group	3 - Not classifiable
Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
Hydrochloric acid (7647-01-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Ethanol (64-17-5)	
Viscosity, kinematic	1,492 mm ² /s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : No additional information available

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)	
LC50 - Fish [1]	12 – 16 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
LC50 - Other aquatic organisms [1]	5012 mg/l 48 hours- daphnia
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Dansac Skin Lotion

Safety Data Sheet

Ethanol (64-17-5)	
EC50 - Crustacea [2]	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Other aquatic organisms [1]	5012 mg/l waterflea
EC50 - Other aquatic organisms [2]	275 mg/l
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	275 mg/l Source: ECHA
ErC50 other aquatic plants	4432 mg/l
NOEC (acute)	9,6 mg/l Daphnia magna
NOEC (chronic)	9,6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
NOEC chronic crustacea	9,6 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0,35 (at 24 °C (at pH 7.4))

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : No information available.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose of in accordance with relevant local regulations.






SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1987	UN 1987	UN 1987	UN 1987	UN 1987
14.2. UN proper shipping name				
ALCOHOLS, N.O.S. (Ethanol)	ALCOHOLS, N.O.S. (Ethanol)	Alcohols, n.o.s. (Ethanol)	ALCOHOLS, N.O.S. (Ethanol)	ALCOHOLS, N.O.S. (Ethanol)


Dansac Skin Lotion

Safety Data Sheet

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
Consult the associated transport regulations for available and applicable exceptions or exemptions.				
The suitable shipping classification must be evaluated at the time of shipment due to the possibility for variations in regard to the transportation of this material considering the requirements, modes of transport, packaging, packaging configuration, quantity etc. Please consult the appropriate regulation for specific shipping information and requirements.				
This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation information can be obtained through the authorized transporting corporation. It is the responsibility of the transporting corporation to follow all applicable laws, regulations and rules relating to the transportation of this product.				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E

Transport by sea

Special provisions (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D

Dansac Skin Lotion

Safety Data Sheet

Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3, A180
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 274, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 274, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction List)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Dansac Skin Lotion

Safety Data Sheet

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
WGK remark	: Most stringent classification due to insufficient data.
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: Ethanol is listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: Ethanol is listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: Ethanol is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: Ethanol is listed

Denmark

Class for fire hazard	: Class II-1
Store unit	: 5 liter
Classification remarks	: R10 <H226>; Emergency management guidelines for the storage of flammable liquids must be followed

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	Overland transport (ADR)
ATE	ATE - acute toxicity estimate
BCF	BCF - bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)

Dansac Skin Lotion

Safety Data Sheet

Abbreviations and acronyms:	
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Effective concentration for 50 percent of test population (median effective concentration)
EN	European Standard
IARC	IARC (International Agency for Research on Cancer)
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)
LD50	Lethal dose for 50 percent of test population (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	PBT - Persistent, Bioaccumulative and Toxic substance
PNEC	Predicted No-Effect Concentration
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways
SDS	SDS - Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	vPvB - Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Sources of Key data : Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens).

Other information : None.

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

Dansac Skin Lotion

Safety Data Sheet

Full text of H- and EUH-statements:

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
--------------	------	-----------------------

Safety Data Sheet (SDS), EU

The information contained in this Safety Data Sheet (SDS) is offered as a guide to the use and handling of this material. All safety aspects of all Hollister products are thoroughly evaluated prior to commercialization. This SDS has been prepared in good faith by technically knowledgeable personnel. Hollister Incorporated shall not be held liable for any damages, losses or injuries of any nature which may result from the use of or reliance upon any information contained in this SDS. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).